

**CITROËN 2CV 2CV 6 CLUB (1984-1991)****ENGINE A06/635**

Capacity: 2,4 liter, Filter capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>	

*Check every 3000 km, change every 10000 km/ 12 months***TRANSAXLE MANUAL 4/1**

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>	<b>Gearlube GL-4 80W-90</b>

*Check every 10000 km, change every 40000 km/ 24 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>LHM +</b>		

*Change every 40000 km/ 48 months***GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 10000 km***GREASE POINTS/NIPPLES FRONT SUSPENSION**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Bi-Turbo 15W-40</b>	<b>HDX 20W-50</b>

*Check every 10000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.