PRODUCT RECOMMENDATION

CITROËN C3 A51 C3 1.6 VTI (2009-2011)

ENGINE EP6C
Capacity: 3,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Avanza MSP 0W-30	**Presteza MSP 5W-30**	**Avanza MSP+ 5W-30**

Check every 2000 km, change every 30000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Avanza MSP 0W-30	**Presteza MSP 5W-30**	**Avanza MSP+ 5W-30**

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC AL4 4/1
Capacity: 5,8 liter (Dry fill), Capacity: 3 liter (Service fill)

USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

TRANSAXLE MANUAL MA5 5/1
Capacity: 2,1 liter (Dry fill), Capacity: 2 liter (Service fill)

USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
SP Gear 5015	**Gearlube RPC 75W-80**	

Check every 60000 km

HYDRAULIC BRAKE SYSTEM ABS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 30000 km, change every 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CITROËN C3 A51 C3 1.6 VTI (2009-2011)

COOLING SYSTEM
Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 2000 km, change every 120000 km/ 60 months

AIRCONDITIONING COMPRESSOR
Capacity: 135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367