

CITROËN C4 PICASSO C4 PICASSO 1.6 THP (110 KW) 5FX (2008-2011)



MOTOR EP6DT
Kapacitet: 4,25 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Avanza MSP 0W-30

Skift alle 30000 km/ 24 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
Avanza MSP 0W-30

Skift alle 20000 km

TRANSAKSEL AUTOMATISK AL4 4/1
Kapacitet: 3 liter (Servicepåfyldning), Kapacitet: 5,85 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Kontroller alle 60000 km

TRANSAKSEL AUTOMATISK AM6 6/1
Kapacitet: 3-4 liter (Servicepåfyldning), Kapacitet: 7 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 4026

TRANSAKSEL AUTOMATISK MCP 6/1
Kapacitet: 2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

PRODUKTANBEFALING 2
Gearlube RPC 75W-80

CITROËN C4 PICASSO C4 PICASSO 1.6 THP (110 KW) 5FX (2008-2011)



TRANSAKSEL MANUEL MCM 6/1

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

GEARKASSE FOR HYDRAULISK AKTIVERING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3023		

HYDRAULISK BREMSESYSTEM ABS

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 6,2 liter, Kapacitet: 6,4 liter (+ automatisk transmission/transaksel)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.