

PRODUCT RECOMMENDATION

CITROËN C4 C4 2.0 16V (130 KW) (2004-2008)



ENGINE XU10J4S
Capacity: 5,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|--------------------------|--------------------------|
| Specialsynth MSP 5W-40 | Emperol 5W-40 | Asyntho 5W-30 |

Change every 20000 km/ 24 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|--------------------------|--------------------------|
| Specialsynth MSP 5W-40 | Emperol 5W-40 | Asyntho 5W-30 |

Change every 15000 km

TRANSAXLE MANUAL BE4/5 5/1
Capacity: 1,9 liter (Dry fill), Capacity: 1,8 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|----------------------------|--|
| SP Gear 5015 | Gearlube RPC 75W-80 | |

Check every 20000 km/ 24 months

HYDRAULIC BRAKE SYSTEM ABS

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|----------------------------------|---------------------------|--|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Change every 24 months

POWER STEERING

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Fluid 3013 | | |

Check every 20000 km/ 24 months

CITROËN C4 C4 2.0 16V (130 KW) (2004-2008)



COOLING SYSTEM

Capacity: 6,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 20000 km/ 24 months

AIRCONDITIONING COMPRESSOR

Capacity: 135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.