

CITROËN C5 X7 C5 2.2 HDI DPF (150 KW) (2009-2011)

**ENGINE DW12C**

Capacity: 5,25 liter (->04/2011), Capacity: 4,85 liter (04/2011->), Filter capacity: 0,25 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| Avanza MSP 0W-30 | Presteza MSP 5W-30 | Avanza MSP+ 5W-30 |

*Change every 30000 km/ 24 months***TRANSAXLE AUTOMATIC AM6 6/1**

Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)

| USE | CLIMATE |
|-----------------|----------|
| Filled for life | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 4036 | | |

*Check every 24 months/ 30000 km***TRANSAXLE MANUAL ML6C 6/1**

Capacity: 1,9 liter (carter/oil pan with ribs), Capacity: 2,6 liter (carter/oil pan without ribs), Capacity: 2,2 liter (Dry fill, carter/oil pan with ribs), Capacity: 2,9 liter (Dry fill, carter/oil pan without ribs)

| USE | CLIMATE |
|-----------------|----------|
| Filled for life | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|----------------------------|--|
| SP Gear 5015 | Gearlube RPC 75W-80 | |

*Check every 60000 km/ 24 months***HYDRAULIC SYSTEM POWER STEERING/LEVELLING**

Capacity: 4,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Fluid 3013 | | |

*Check every 30000 km/ 24 months, change every 200000 km/ 60 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|----------------------------------|---------------------------|--|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Change every 24 months

CITROËN C5 X7 C5 2.2 HDI DPF (150 KW) (2009-2011)



GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 20000 km/ 24 months

COOLING SYSTEM

Capacity: 10,8 liter, Capacity: 11,8 liter (with 4 zone airconditioning system)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |

Check every 24 months/ 30000 km

PARTICLE FILTER ADDITIVE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.