

CITROËN C8 C8 2.0 HDI 16V DPF (2002-2006)**ENGINE DW10ATED4 (RHW)**

Capacity: 4,75 liter

| USE | | CLIMATE |
|---------------------------|--------------------------|--------------------------|
| Severe (preferred) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Presteza MSP 5W-30 | Avanza MSP+ 5W-30 | Avanza RPC 5W-30 |

Change every 15000 km/ 12 months

| USE | | CLIMATE |
|-------------------------------|--------------------------|--------------------------|
| Normal (alternative) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Specialsynth MSP 5W-40 | Emperol 5W-40 | Asyntho 5W-30 |

Change every 20000 km/ 24 months

| USE | | CLIMATE |
|---------------------------|--------------------------|--------------------------|
| Normal (preferred) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Presteza MSP 5W-30 | Avanza MSP+ 5W-30 | Avanza RPC 5W-30 |

Change every 20000 km/ 24 months

| USE | | CLIMATE |
|-------------------------------|--------------------------|--------------------------|
| Severe (alternative) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Specialsynth MSP 5W-40 | Emperol 5W-40 | Asyntho 5W-30 |

*Change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC AL4 4/1**

Capacity: 6 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 2032 | | |

*Check every 60000 km***TRANSAXLE MANUAL ML5 5/1**

Capacity: 2 liter

| USE | | CLIMATE |
|--------------------------|----------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 5015 | Gearlube RPC 75W-80 | |

Check every 60000 km

**HYDRAULIC BRAKE SYSTEM ABS**

Capacity: 0,66 liter

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

*Check every 20000 km/ 24 months, change every 24 months***POWER STEERING**

Capacity: 1,3 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |

Check every 20000 km/ 24 months

| USE | | CLIMATE |
|--------------------------|--|----------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |

*Check every 15000 km***COOLING SYSTEM**

Capacity: 10,2 liter (+ automatic transmission/transaxle), Capacity: 10 liter (+ manual transmission/transaxle)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |

Check every 20000 km/ 24 months

| USE | | CLIMATE |
|--------------------------|--|----------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |

*Check every 15000 km***PARTICLE FILTER ADDITIVE SYSTEM**

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.