

# CITROËN EVASION / SYNERGIE EVASION / SYNERGIE 2.0i (1996-1997)

**ENGINE XU10J2C**

Capacity: 4,75 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Specialsynth MSP 5W-40</b>	<b>Emperol 5W-40</b>	<b>Asyntho 5W-30</b>

*Change every 15000 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Gearlube RPC 75W-80</b>	

*Check every 15000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 15000 km/ 12 months, change every 60000 km/ 24 months***POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 15000 km/ 12 months***COOLING SYSTEM**

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Check every 15000 km/ 12 months, change every 120000 km/ 24 months*

# CITROËN EVASION / SYNERGIE EVASION / SYNERGIE 2.0i (1996-1997)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*