CITROËN SAXO SAXO 1.4I (1996-1998)



ENGINE TU3JP Capacity: 3,5 liter, Filter capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30
Change every 15000 km/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30

CLIMATE
Moderate

Check every 15000 km/ 12 months, change every 30000 km

Check every 3000 km, change every 10000 km/12 months

TRANSAXLE MANUAL 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	
Check every 15000 km/ 12 months	•	

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 15000 km/ 12 months, ch	ange every 60000 km/ 24 months	1

CITROËN SAXO SAXO 1.4I (1996-1998)



HYDRAULIC BRAKE SYSTEM ABS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 15000 km/ 12 months, change every 60000 km/ 24 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Chook ayang 15000 km/12 months	<u>.</u>

Check every 15000 km/ 12 months

COOLING SYSTEM Capacity: 6,1 liter		
USE	CLIMATE	E
Normal	Mode	rate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 15000 km/12 months, change every 120000 km/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.