

**CITROËN VISA VISA 17 D, RD (1984-1988)****ENGINE 161/A**

Capacity: 5 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40***Change every 7500 km/ 12 months*

USE	CLIMATE
Normal	Arctic

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Change every 7500 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W**

## PRODUCT RECOMMENDATION 3

**Gearlube GL-4 80W-90***Check every 7500 km, change every 97500 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,29 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 45000 km/ 24 months***COOLING SYSTEM**

Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

**CITROËN VISA VISA 17 D, RD (1984-1988)****VACUUM PUMP**

Capacity: 0,04 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Check every 7500 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*