## **CITROËN XM XM 2.0I** (1989-1993)



ENGINE XU10J2 (R6A)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 10W-40	Bi-Turbo 15W-40	

Check every 3000 km, change every 10000 km/12 months

USE CLIM Normal Mod PRODUCT RECOMMENDATION 1	
	ATE .
PRODUCT RECOMMENDATION 4	erate
PRODUCT RECOmmendation 1	
ATF Dexron II-D	

Check every 10000 km, change every 20000 km

TRANSAXLE MANUAL 5/1 Capacity: 1,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube RPC 75W-80		

Check every 10000 km

HYDRAULIC SYSTEM POWER STEERING/BRAKE BOOSTER/LEVELLING Capacity: 4,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		
Change every 60000 km		,

COOLING SYSTEM Capacity: 7,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	·

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

## PRODUCT RECOMMENDATION

## **CITROËN XM XM 2.0I** (1989-1993)



information contained herein is subject to changes without notification.