CITROËN XM XM V6-24 3.0 (1994-1997)



ENGINE ZPJ4 Capacity: 6,5 liter, Filter capacity: 0,5 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30		

Change every 15000 km/ 12 months

TRANSAXLE AUTOMATIC MG5T Capacity: 2,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Change every 15000 km

TRANSAXLE MANUAL 5/1 Capacity: 1,85 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

Check every 60000 km

HYDRAULIC SYSTEM POWER STEERING/BRAKE BOOSTER/LEVELLING Capacity: 5,4 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
LHM +				

Check every 15000 km, change every 60000 km

COOLING SYSTEM Capacity: 12 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the PRODUCT RECOMMENDATION

CITROËN XM XM V6-24 3.0 (1994-1997)



information contained herein is subject to changes without notification.