CITROËN XSARA PICASSO XSARA PICASSO 1.6 HDI DPF (2009-2011)



ENGINE DV6TED4 Capacity: 3,8 liter				
USE		climate Moderate		
Normal (alternative)				
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Specialsynth MSP 5W-40	Emperol 5W-40	Emperol 10W-40		
Change every 20000 km/ 12 months				
USE		CLIMATE		
Normal (preferred)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30		
Change every 20000 km/ 12 months	,			

TRANSAXLE MANUAL BE4 5/1 Capacity: 1,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 5015	Gearlube RPC 75W-80			
Check every 20000 km/ 12 months		'		

HYDRAULIC BRAKE SYSTEM ABS				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Check every 20000 km/ 12 months, change every 60000 km/ 24 months				

POWER STEERING		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 20000 km/ 12 months		

PRODUCT RECOMMENDATION

CITROËN XSARA PICASSO XSARA PICASSO 1.6 HDI DPF (2009-2011)



COOLING SYSTEM Capacity: 11 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Chack even 20000 km/12 months, change even 120000 km/60 months			

Check every 20000 km/12 months, change every 120000 km/60 months

PARTICLE FILTER ADDITIVE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.