

CITROËN XSARA XSARA 1.8i (74 KW) (1999-2001)



ENGINE XU7JP
Capacity: 4,8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Specialsynth MSP 5W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Asyntho 5W-30

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC 4/1
Capacity: 2,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 20000 km/ 12 months, change every 40000 km/ 48 months

HYDRAULIC BRAKE SYSTEM

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 20000 km/ 12 months, change every 60000 km/ 24 months

HYDRAULIC BRAKE SYSTEM ABS

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 20000 km/ 12 months, change every 60000 km/ 24 months

POWER STEERING

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 20000 km/ 12 months

CITROËN XSARA XSARA 1.8i (74 KW) (1999-2001)

**COOLING SYSTEM**

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 20000 km/ 12 months, change every 120000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.