

DAIHATSU CHARADE CHARADE 1.3 (1993-1996)

**ENGINE HC-C**

Capacity: 3,5 liter, Capacity: 3,6 liter (+ oil cooler)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

HDX 20W-50*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Classic Racing Oil 15W-50*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Check every 3000 km, change every 10000 km/ 12 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 3,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 20000 km/ 12 months, change every 80000 km/ 48 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90*Check every 20000 km/ 12 months, change every 80000 km/ 48 months*

DAIHATSU CHARADE CHARADE 1.3 (1993-1996)**HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 1000 km, change every 12 months

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 1000 km

COOLING SYSTEM

Capacity: 4,7 liter, Capacity: 4,6 liter (with automatic transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 1000 km, change every 40000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.