

**DAIHATSU MOVE MOVE (1999-2003)****ENGINE EJ-DE**

Capacity: 2,3 liter, Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Check every 1000 km, change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Check every 1000 km, change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC 3/1**

Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 2032**

## PRODUCT RECOMMENDATION 2

**ATF Almirol**

## PRODUCT RECOMMENDATION 3

**ATF Dexron II-D***Check every 15000 km/ 12 months, change every 90000 km/ 72 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015**

## PRODUCT RECOMMENDATION 3

**Syngear TDL 75W-90***Check every 15000 km/ 12 months, change every 90000 km/ 72 months***HYDRAULIC BRAKE SYSTEM ABS AS OPTION**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

## PRODUCT RECOMMENDATION 3

**Drauliquid DOT 3***Check every 15000 km/ 12 months, change every 90000 km/ 48 months*

**DAIHATSU MOVE MOVE (1999-2003)****POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

*Check every 15000 km/ 12 months*

**COOLING SYSTEM**

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Check every 15000 km/ 12 months, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*