DODGE (USA / CAN) CALIBER PM CALIBER 2.4 (2010-2012)

ENGINE Capacity: 4,3 liter		
USE		**CLIMATE**
Normal		Moderate
PRODUCT RECOMMENDATION 1 **Duranza ECO 5W-20**		

Change every 8000 miles/ 6 months

TRANSAXLE CVT 1/1 Capacity: 8,1 liter (Dry fill), Capacity: 7 liter (Service fill)		
USE		**CLIMATE**
Normal		Moderate
PRODUCT RECOMMENDATION 1 **SP Matic 4016**		

Change every 120000 miles/ 90 months

USE		**CLIMATE**
Severe		Moderate
PRODUCT RECOMMENDATION 1 **SP Matic 4016**		

Change every 64000 miles/ 48 months

TRANSAXLE MANUAL 5/1		
USE		**CLIMATE**
Severe		Moderate
PRODUCT RECOMMENDATION 1 **SP Matic 4026**		

Change every 48000 miles/ 48 months

HYDRAULIC BRAKE SYSTEM		
USE		**CLIMATE**
Normal		Moderate
PRODUCT RECOMMENDATION 1 **Drauliquid DOT 3**		

DODGE (USA / CAN) CALIBER PM CALIBER 2.4 (2010-2012)

POWER STEERING	
USE	**CLIMATE**
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	

COOLING SYSTEM Capacity: 6,8 liter	
USE	**CLIMATE**
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	

Change every 104000 miles/ 60 months

AIRCONDITIONING SYSTEM Capacity: 510 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.