

DODGE (USA / CAN) CHALLENGER LA

CHALLENGER 6.4 SRT 392 (2014-2015)



ENGINE HEMI
Capacity: 6,6 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 6000 miles/ 6 months

DIFFERENTIAL REAR LIMITED SLIP
Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

Check every 18000 miles/ 18 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

Change every 48000 miles/ 48 months

TRANSMISSION AUTOMATIC 8HP70 8/1
Capacity: 8,5 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034

TRANSMISSION MANUAL TR6060 6/1
Capacity: 3,2 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 24000 miles/ 18 months, change every 48000 miles/ 48 months

DODGE (USA / CAN) CHALLENGER LA

CHALLENGER 6.4 SRT 392 (2014-2015)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

COOLING SYSTEM

Capacity: 14,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 150000 miles/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.