DODGE (USA / CAN) CHARGER LD CHARGER 5.7 AWD (2012-2014)



ENGINE HEMI Capacity: 6,6 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Duranza ECO 5W-20	
Change every 10000 miles/ 12 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Duranza ECO 5W-20	
Change every 4000 miles	

DIFFERENTIAL FRONT Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Check every 20000 miles/ 24 month	ns	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90 Syngear 75W-90 **SP Gear 1011**

Change every 40000 miles/ 48 months

DIFFERENTIAL REAR Capacity: 1,1-1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Check every 20000 miles/ 24 months, change every 4000	0 miles/ 48 months

Check every 20000 miles/24 months, change every 40000 miles/48 months

DODGE (USA / CAN) CHARGER LD CHARGER 5.7 AWD (2012-2014)



TRANSFERBOX Borg Warner 44-40 Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Check every 30000 miles/ 36 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Change every 60000 miles/ 72 months		

Capacity: 7,7 liter (Dry fill), Capacity: 5 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 144 months/ 120000 miles		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 60000 miles/ 72 months		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

DODGE (USA / CAN) CHARGER LD CHARGER 5.7 AWD (2012-2014)



COOLING SYSTEM Capacity: 13,9-14,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 150000 miles/ 120 n	nonths	•

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.