

DODGE (USA / CAN) CHARGER LX

CHARGER 6.1 SRT8 (2006-2009)



ENGINE HEMI
Capacity: 6,6 liter

USE	CLIMATE
Preferred, flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 6000 miles/ 6 months

USE	CLIMATE
Flexible, alternative (max)	Moderate

PRODUCT RECOMMENDATION 1

Specialsynth MSP 5W-40

Change every 6000 miles/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 3000 miles/ 3 months

USE	CLIMATE
Severe (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Specialsynth MSP 5W-40

Change every 3000 miles/ 3 months

DIFFERENTIAL REAR 198 MM RII
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2

Gearlube HS GL-5 80W-140

Check every 18000 miles/ 18 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2

Gearlube HS GL-5 80W-140

Change every 48000 miles/ 48 months

DODGE (USA / CAN) CHARGER LX

CHARGER 6.1 SRT8 (2006-2009)



DIFFERENTIAL REAR 210 MM RII
Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Check every 18000 miles/ 18 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Change every 48000 miles/ 48 months

DIFFERENTIAL REAR 215 MM RII
Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Check every 18000 miles/ 18 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Change every 48000 miles/ 48 months

TRANSMISSION AUTOMATIC NAG1 (W5A580)
Capacity: 7,7 liter (Overhaul capacity), Capacity: 5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 120000 miles/ 120 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 60000 miles/ 60 months

DODGE (USA / CAN) CHARGER LX

CHARGER 6.1 SRT8 (2006-2009)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

COOLING SYSTEM

Capacity: 14,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Change every 102000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.