

DODGE (USA / CAN) MAGNUM LX MAGNUM

6.1 V8 SRT-8 (USA) (2005-2007)



ENGINE HEMI
Capacity: 6,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 6000 miles/ 6 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 3000 miles/ 3 months

DIFFERENTIAL REAR 198 MM RII
Capacity: 1,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2

Gearlube HS GL-5 80W-140

Change every 48000 miles

USE
Severe

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

USE
Severe

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071

DODGE (USA / CAN) MAGNUM LX MAGNUM

6.1 V8 SRT-8 (USA) (2005-2007)


DIFFERENTIAL REAR 210 MM RII

Capacity: 1,6 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Change every 48000 miles

DIFFERENTIAL REAR 215 MM RII

Capacity: 1,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Gearlube HS GL-5 80W-140	

Change every 48000 miles

TRANSMISSION AUTOMATIC NAG1 (W5A580)

Capacity: 7,7 liter (Overhaul capacity), Capacity: 5 liter (Service fill)

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 60000 miles

DODGE (USA / CAN) MAGNUM LX MAGNUM 6.1 V8 SRT-8 (USA) (2005-2007)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 60000 miles

COOLING SYSTEM

Capacity: 14 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Change every 102000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.