

DODGE (USA / CAN) NEON / SX PL NEON

2.4 16V TURBO SRT-4 (USA) (2002-2005)



ENGINE (148 ci) Turbo
Capacity: 4,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

Change every 5000 miles/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

Change every 3000 miles

TRANSAXLE MANUAL NV T850 5/1
Capacity: 2,3-2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 48000 miles

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Change every 48000 miles

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Change every 48000 miles

DODGE (USA / CAN) NEON / SX PL NEON

2.4 16V TURBO SRT-4 (USA) (2002-2005)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

COOLING SYSTEM

Capacity: 7,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Change every 100000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.