

DODGE (USA / CAN) NITRO KA NITRO 3.7 V6 (2007-2010)

**ENGINE**

Capacity: 4,7 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20***Change every 6000 miles/ 6 months***DIFFERENTIAL REAR**

Capacity: 2,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube Racing 75W-140****PRODUCT RECOMMENDATION 2****Gearlube HS GL-5 80W-140***Check every 18000 miles/ 18 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube Racing 75W-140****PRODUCT RECOMMENDATION 2****Gearlube HS GL-5 80W-140***Change every 18000 miles/ 18 months***TRANSMISSION AUTOMATIC 42RLE 4/1**

Capacity: 8,3 liter (Overhaul capacity), Capacity: 3,8 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Change every 120000 miles/ 120 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Change every 60000 miles/ 60 months*

DODGE (USA / CAN) NITRO KA NITRO 3.7 V6 (2007-2010)



TRANSMISSION MANUAL NSG370 6/1

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Change every 30000 miles/ 30 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

COOLING SYSTEM

Capacity: 13,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Change every 102000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.