

FIAT (EU) CINQUECENTO 170 CINQUECENTO 700 (1992-1998)



MOTOR 170A.046

Kapacitet: 2,25 liter, Filterkapacitet: 0,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

Kontroller alle 500 km, skift alle 15000 km/ 12 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Emperol 10W-40

Kontroller alle 500 km, skift alle 15000 km/ 12 måneder

TRANSAKSEL MANUEL 4/1

Kapacitet: 1,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Kontroller alle 45000 km/ 36 måneder, skift alle 120000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 500 km, skift alle 24 måneder

SMØREPUNKTER/NIPLER KARDANAKSLENS SAMLINGER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

FIAT (EU) CINQUECENTO 170 CINQUECENTO 700 (1992-1998)



KØLESYSTEM

Kapacitet: 4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 500 km, skift alle 60000 km/ 24 måneder

STYRETØJ

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.