

FIAT (EU) FREEMONT 345 FREEMONT 2.0 MULTIJET AWD (125 KW) (2011-2016)



MOTOR

Kapacitet: 5,2 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Avanza MSP+ 5W-30

PRODUKTANBEFALING 3

Avanza RPC 5W-30

Kontroller alle 3000 km, skift alle 24 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Avanza MSP+ 5W-30

PRODUKTANBEFALING 3

Avanza RPC 5W-30

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

Skift alle 80000 km/ 48 måneder

TRANSAKSEL AUTOMATISK 6/1

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 160000 km/ 96 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 80000 km/ 48 måneder

FIAT (EU) FREEMONT 345 FREEMONT 2.0 MULTIJET AWD (125 KW) (2011-2016)



TRANSFERBOKS (PTU)

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

Skift alle 80000 km/ 48 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 30000 km/ 24 måneder

SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

KØLESYSTEM

Kapacitet: 9,1-9,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.