

FIAT (EU) GRANDE PUNTO 199 GRANDE PUNTO 1.3 MULTIJET (66 KW) (2005-2009)



MOTOR 199A3000

Kapacitet: 3,2 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 5W-40

Skift alle 30000 km/ 24 måneder

HYDRAULISK AKTIVERING GEARKASSE

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3023

TRANSAKSEL HALVAUTOMATISK M20 6/1

Kapacitet: 1,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

TRANSAKSEL MANUEL C 510.5 5/1

Kapacitet: 1,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 12 måneder/ 30000 km

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

FIAT (EU) GRANDE PUNTO 199 GRANDE PUNTO 1.3 MULTIJET (66 KW) (2005-2009)



SMØREPUNKTER/NIPLER AFFJEDRING FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

SMØREPUNKTER/NIPLER HJULLEJER BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

SMØREPUNKTER/NIPLER HJULLEJER FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

SMØREPUNKTER/NIPLER HOMOKINETISKE LED DIFFERENTIALESIDE

Kapacitet: 150 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER HOMOKINETISKE LED HJULSIDE

Kapacitet: 95 gram

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 7,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 12 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.