

FIAT (EU) PANDA 169 PANDA 1.2 (44 KW) LPG (2003-2010)



MOTOR 188A4000 LPG
Kapacitet: 2,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Specialsynth MSP 5W-40

Skift alle 20000 km

TRANSAKSEL MANUEL 5/1
Kapacitet: 1,65 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

Kontroller alle 80000 km

HYDRAULISK BREMSESYSYSTEM ABS
Kapacitet: 0,55 kg

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Kontroller alle 20000 km, skift alle 60000 km/ 24 måneder

SMØREPUNKTER/NIPLER HOMOKINETISKE LED DIFFERENTIALESIDE
Kapacitet: 100 gram (Tør efterfyld)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER HOMOKINETISKE LED HJULSIDE
Kapacitet: 80 gram (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

FIAT (EU) PANDA 169 PANDA 1.2 (44 KW) LPG (2003-2010)



KØLESYSTEM

Kapacitet: 4,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.