

FIAT (EU) PUNTO 176 PUNTO 85 16V (1997-1999)



MOTOR 176B9000

Kapacitet: 3,75 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

Kontroller alle 500 km, skift alle 15000 km/ 18 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Duranza LSP 5W-30

PRODUKTANBEFALING 2

Asyntho 5W-30

Kontroller alle 500 km, skift alle 15000 km/ 18 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 1,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 60000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 500 km, skift alle 60000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 500 km

FIAT (EU) PUNTO 176 PUNTO 85 16V (1997-1999)



KØLESYSTEM

Kapacitet: 4,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 500 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.