

FIAT (EU) PUNTO 188 PUNTO 1.2 8V (2003-2010)



MOTOR 188A4000
Kapacitet: 2,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Emperol 10W-40		

Kontroller alle 3000 km, skift alle 20000 km/ 12 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Duranza LSP 5W-30	Asyntho 5W-30	

Kontroller alle 3000 km, skift alle 20000 km/ 12 måneder

ELEKTRONISK/HYDRAULISK GEARKASSEENHED
Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3023		

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km

TRANSAKSEL MANUEL 5/1
Kapacitet: 1,65 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 80000 km

HYDRAULISK BREMSESYSTEM
Kapacitet: 0,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 1000 km, skift alle 60000 km/ 24 måneder

FIAT (EU) PUNTO 188 PUNTO 1.2 8V (2003-2010)



KØLESYSTEM

Kapacitet: 4,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 20000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.