

FIAT (EU) PUNTO 199 PUNTO 1.4 (57 KW) (2011-2019)



MOTOR 350A1000
Kapacitet: 2,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Helar MSP+ 5W-40

PRODUKTANBEFALING 2
Specialsynth MSP 5W-40

Skift alle 30000 km/ 12 måneder

HYDRAULISK AKTIVERING GEARCASE
Kapacitet: 0,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Fluid 3023

TRANSAKSEL HALVAUTOMATISK 5/1
Kapacitet: 1,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1081

PRODUKTANBEFALING 2
SP Gear 5015

TRANSAKSEL MANUEL C514.5 5/1
Kapacitet: 1,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1081

PRODUKTANBEFALING 2
SP Gear 5015

Kontroller alle 12 måneder/ 30000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

FIAT (EU) PUNTO 199 PUNTO 1.4 (57 KW) (2011-2019)



KØLESYSTEM

Kapacitet: 5,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 12 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.