

FIAT (EU) TIPO 160 TIPO 2.0 16V (1991-1995)



MOTOR 160A8.046

Kapacitet: 5,2 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Kontroller alle 45000 km/ 36 måneder, skift alle 120000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,41 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 500 km, skift alle 24 måneder

HYDRAULISK BREMSESYSTEM ABS

Kapacitet: 0,53 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 500 km, skift alle 24 måneder

FIAT (EU) TIPO 160 TIPO 2.0 16V (1991-1995)



SERVOSTYRING

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 15000 km/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 6,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 500 km, skift alle 60000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.