

FIAT (EU) ULYSSE 179 ULYSSE 3.0 V6 24V (2002-2005)



MOTOR XFW

Kapacitet: 4,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

Kontroller alle 1000 km, skift alle 30000 km

TRANSAXSEL AUTOMATISK 4/1

Kapacitet: 8 liter (Førstegangsopfyldning), Kapacitet: 3 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Dexron II-D

Kontroller alle 60000 km

HYDRAULISK BREMSESYSYSTEM ABS

Kapacitet: 0,62 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 30000 km/ 12 måneder, skift alle 60000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUKTANBEFALING

FIAT (EU) ULYSSE 179 ULYSSE 3.0 V6 24V (2002-2005)



information contained herein is subject to changes without notification.