FIAT (EU) 500 312 500 1.4 16V (74 KW) (2007-2014)



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	
Change every 30000 km/ 12 montl	hs	
USE		CLIMATE
Severe		Moderate
	PRODUCT RECOMMENDATION 2	
PRODUCT RECOMMENDATION 1		I

HYDRAULIC ACTUATION GEARBOX Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3023	

TRANSAXLE MANUAL 6/1 Capacity: 1,65 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		

TRANSAXLE SEMI-AUTOMATIC 5/1 Capacity: 1,65 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		

PRODUCT RECOMMENDATION

FIAT (EU) 500 312 500 1.4 16V (74 KW) (2007-2014)



HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
01 1 000001 1	20000 1 / 2 4 11		

Check every 30000 km, change every 60000 km/24 months

COOLING SYSTEM Capacity: 4,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 30000 km	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.