

FIAT (EU) 500L 351, 352 500L 0.9 TWINAIR TURBO (63 KW) CNG (2013-2019)



ENGINE 312A2000 CNG
Capacity: 3,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Specialsynth MSP 5W-40

Change every 30000 km/ 24 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Specialsynth MSP 5W-40

Change every 12 months

TRANSAXLE MANUAL 6/1
Capacity: 1,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

PRODUCT RECOMMENDATION 2

SP Gear 5015

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 24 months

COOLING SYSTEM
Capacity: 5,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.