FIAT (EU) BRAVO 198 BRAVO 1.4 16V 90 (2007 - 2015)



ENGINE 192B2000 Capacity: 2,9 liter, Filter capacity: 0,15 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Helar MSP+ 5W-40	Specialsynth MSP 5W-40		
Change every 30000 km/ 24 months	•	·	

use Severe		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	

Check every 3000 km, change every 10000 km/ 12 months

TRANSAXLE MANUAL 6/1 Capacity: 1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 525 grams (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 30000 km, change every 60000 km/24 months

GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE Capacity: 100 grams (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE Capacity: 90 grams (Dry fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

FIAT (EU) BRAVO 198 BRAVO 1.4 16V 90 (2007-2015)



COOLING SYSTEM Capacity: 5,2 liter (Dry fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

Check every 30000 km

AIRCONDITIONING Capacity: 500 grams (Dry fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR Denso SCS 06 Capacity: 130 CM3 (Dry fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.