

# FIAT (EU) CINQUECENTO 170

## CINQUECENTO 900 (1992-1998)

**ENGINE 170A1046**

Capacity: 3,75 liter, Filter capacity: 0,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40***Check every 500 km, change every 15000 km/ 12 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Check every 500 km, change every 15000 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W***Check every 45000 km/ 36 months, change every 120000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 500 km, change every 24 months***GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

# FIAT (EU) CINQUECENTO 170

## CINQUECENTO 900 (1992-1998)

**COOLING SYSTEM**

Capacity: 4,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 500 km, change every 60000 km/ 24 months***STEERING GEAR**

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*