

# FIAT (EU) DOBLÒ 223 DOBLÒ 1.3 MULTIJET

## 16V (55 KW) (2005-2009)



**ENGINE** 199A2000  
Capacity: 3 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Specialsynth MSP 5W-40</b>	<b>Emperol 5W-40</b>	<b>Asyntho 5W-30</b>

*Check every 1000 km, change every 30000 km/ 24 months*

**TRANSAXLE MANUAL** 5/1  
Capacity: 1,98 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>SP Gear 1071</b>	

*Check every 80000 km*

**HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**  
Capacity: 0,45 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 20000 km, change every 60000 km/ 24 months*

**POWER STEERING**  
Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 20000 km*

**COOLING SYSTEM**  
Capacity: 6,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

*Check every 20000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is*

PRODUCT RECOMMENDATION

**FIAT (EU) DOBLÒ 223 DOBLÒ 1.3 MULTIJET  
16V (55 KW) (2005-2009)**



*advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*