

# FIAT (EU) DOBLÒ 263 DOBLÒ 1.3 MULTIJET (66 KW) (2010-2016)

**ENGINE 199A3000**

Capacity: 3,2 liter, Filter capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 5W-30</b>	<b>Avanza MSP+ 5W-30</b>	<b>Avanza RPC 5W-30</b>

*Change every 30000 km/ 24 months***TRANSAXLE MANUAL 5/1**

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1081</b>	<b>SP Gear 5015</b>	

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 30000 km, change every 60000 km/ 24 months***POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		

USE		CLIMATE
Cold climate		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

# FIAT (EU) DOBLÒ 263 DOBLÒ 1.3 MULTIJET (66 KW) (2010-2016)


**COOLING SYSTEM**

Capacity: 5,2 liter

USE	CLIMATE
Normal	Moderate

**PRODUCT RECOMMENDATION 1**
**Coolant SP 14+**
*Check every 24 months/ 30000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*