FIAT (EU) FREEMONT 345 FREEMONT 2.0 MULTIJET (103 KW) (2011-2016)



ENGINE Capacity: 5,2 liter			
USE		CLIMATE	
Flexible (max)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30	
Check every 3000 km, change every 24 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30	

Check every 3000 km, change every 10000 km/ 12 months

TRANSAXLE MANUAL 6/1 Capacity: 1,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Change every 30000 km/ 24 months

POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4026			

FIAT (EU) FREEMONT 345 FREEMONT 2.0 MULTIJET (103 KW) (2011-2016)



COOLING SYSTEM Capacity: 9,1-9,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Charles years 24 months/ 20000 km		

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.