

FIAT (EU) FREEMONT 345 FREEMONT 2.0 MULTIJET AWD (120 KW) (2011-2016)

**ENGINE**

Capacity: 5,2 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Avanza MSP+ 5W-30****PRODUCT RECOMMENDATION 3****Avanza RPC 5W-30***Check every 3000 km, change every 24 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Avanza MSP+ 5W-30****PRODUCT RECOMMENDATION 3****Avanza RPC 5W-30***Check every 3000 km, change every 10000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 0,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube Racing 75W-140***Change every 80000 km/ 48 months***TRANSAXLE AUTOMATIC 6/1****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Change every 160000 km/ 96 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Change every 80000 km/ 48 months*

FIAT (EU) FREEMONT 345 FREEMONT 2.0 MULTIJET AWD (120 KW) (2011-2016)



TRANSFERBOX (PTU)

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 80000 km/ 48 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 30000 km/ 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

COOLING SYSTEM

Capacity: 9,1-9,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.