

# FIAT (EU) FREEMONT 345 FREEMONT 2.0 MULTIJET AWD (125 KW) (2011-2016)

**ENGINE**

Capacity: 5,2 liter

| USE                       |                          | CLIMATE                  |
|---------------------------|--------------------------|--------------------------|
| Flexible (max)            |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Presteza MSP 5W-30</b> | <b>Avanza MSP+ 5W-30</b> | <b>Avanza RPC 5W-30</b>  |

*Check every 3000 km, change every 24 months*

| USE                       |                          | CLIMATE                  |
|---------------------------|--------------------------|--------------------------|
| Severe                    |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Presteza MSP 5W-30</b> | <b>Avanza MSP+ 5W-30</b> | <b>Avanza RPC 5W-30</b>  |

*Check every 3000 km, change every 10000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 0,7 liter

| USE                            |  | CLIMATE  |
|--------------------------------|--|----------|
| Normal                         |  | Moderate |
| PRODUCT RECOMMENDATION 1       |  |          |
| <b>Gearlube Racing 75W-140</b> |  |          |

*Change every 80000 km/ 48 months***TRANSAXLE AUTOMATIC 6/1**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4026</b>     |  |          |

*Change every 160000 km/ 96 months*

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Severe                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 4026</b>     |  |          |

*Change every 80000 km/ 48 months*

# FIAT (EU) FREEMONT 345 FREEMONT 2.0 MULTIJET AWD (125 KW) (2011-2016)



## TRANSFERBOX (PTU)

Capacity: 0,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

Change every 80000 km/ 48 months

## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

Change every 30000 km/ 24 months

## POWER STEERING

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4026**

## COOLING SYSTEM

Capacity: 9,1-9,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.