## **FIAT (EU) FREEMONT 345 FREEMONT 2.4** (2012-2016)



ENGINE Capacity: 4,3 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Duranza ECO 5W-20	Asyntho 5W-30	

Check every 3000 km, change every 12 months

TRANSAXLE AUTOMATIC 6/1 Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	

TRANSAXLE MANUAL 6/1 Capacity: 1,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change avery 20000 km/24 months		

Change every 30000 km/ 24 months

POWER STEERING	
use Normal	сымате Moderate
PRODUCT RECOMMENDATION 1 SP Matic 4026	

## **FIAT (EU) FREEMONT 345 FREEMONT 2.4** (2012-2016)



COOLING SYSTEM Capacity: 10,1-11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 3000 km, change every 240000 km/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.