FIAT (EU) GRANDE PUNTO 199 GRANDE PUNTO 1.3 MULTIJET (62 KW) ECO (2010-



2011)

| ENGINE 199B4000 Capacity: 3,2 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Flexible (max) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Presteza MSP 5W-30 | Avanza MSP+ 5W-30 | Avanza RPC 5W-30 |

Change every 30000 km/24 months

| TRANSAXLE MANUAL 5/1 Capacity: 1,7 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Gear 5015 | | |
| Check every 12 months/ 30000 km | | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0,5 liter | | | |
|---|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |

| GREASE POINTS/NIPPLES FRONT SUSPENSION | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Labora Grease | | |

GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE

Capacity: 150 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

| GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE Capacity: 95 grams | | |
|--|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

PRODUCT RECOMMENDATION

FIAT (EU) GRANDE PUNTO 199 GRANDE PUNTO 1.3 MULTIJET (62 KW) ECO (2010-2011)



| GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Labora Grease | | |

| GREASE POINTS/NIPPLES WHEEL BEARINGS REAR | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Labora Grease | | |

| COOLING SYSTEM Capacity: 7,4 liter | | |
|------------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |
| Check every 12 months/ 30000 km | | |

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.