

FIAT (EU) PANDA 312, 319 PANDA 0.9 TWINAIR TURBO (63 KW) EURO 5 (2011- 2015)

**ENGINE 312A2000**

Capacity: 3,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar MSP+ 5W-40

PRODUCT RECOMMENDATION 2

Specialsynth MSP 5W-40*Change every 30000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Helar MSP+ 5W-40

PRODUCT RECOMMENDATION 2

Specialsynth MSP 5W-40*Change every 12 months***HYDRAULIC ACTUATION GEARBOX**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023**TRANSAXLE MANUAL 5/1**

Capacity: 1,65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 90000 km/ 72 months***TRANSAXLE SEMI-AUTOMATIC 5/1**

Capacity: 1,65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 90000 km/ 72 months*

PRODUCT RECOMMENDATION

FIAT (EU) PANDA 312, 319 PANDA 0.9 TWINAIR TURBO (63 KW) EURO 5 (2011- 2015)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 60000 km/ 24 months

COOLING SYSTEM

Capacity: 5,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.