

FIAT (EU) PUNTO 188 PUNTO 1.3 MULTIJET (2003-2010)



ENGINE 188A9000
Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

Change every 30000 km/ 12 months

ELECTRONIC/HYDRAULIC GEARBOXUNIT
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023

Check every 20000 km/ 12 months, change every 40000 km

TRANSAXLE MANUAL 5/1
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

Check every 80000 km

HYDRAULIC BRAKE SYSTEM
Capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 20000 km, change every 60000 km/ 24 months

HYDRAULIC BRAKE SYSTEM ABS
Capacity: 0,45 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 20000 km, change every 60000 km/ 24 months

FIAT (EU) PUNTO 188 PUNTO 1.3 MULTIJET (2003-2010)

**COOLING SYSTEM**

Capacity: 6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 14+***Check every 20000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.