

FIAT (EU) PUNTO EVO 199 PUNTO EVO 1.2 (48 KW) (2009-2012)



ENGINE 199A4000
Capacity: 2,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------|-------------------------------|
| Helar MSP+ 5W-40 | Specialsynth MSP 5W-40 |

Change every 30000 km/ 12 months

TRANSAXLE MANUAL 5/1
Capacity: 1,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| SP Gear 5015 | |

Check every 12 months/ 30000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS
Capacity: 0,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|----------------------------------|---------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 |

COOLING SYSTEM
Capacity: 5,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| Coolant SP 14+ | |

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.