FIAT (EU) TIPO 160 TIPO 1.1 (1988-1993)



ENGINE 160A3.000 Capacity: 3,45 liter, Filter capacity: 0,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 15W-40				
Change every 15000 km/ 12 months				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Asyntho 5W-30				
Change every 15000 km/ 12 months				

TRANSAXLE MANUAL 5/1 Capacity: 1,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Check every 45000 km/ 36 months, change every 120000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 500 km, change every 24 months

GREASE POINTS/NIPPLES DRIVE SHAFT JOINTS Capacity: 0,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			

FIAT (EU) TIPO 160 TIPO 1.1 (1988-1993)



COOLING SYSTEM Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Charles your 500 km shares aver 20000 km / 24 months		

Check every 500 km, change every 60000 km/24 months

STEERING GEAR

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.