

FIAT (EU) ULYSSE 179 ULYSSE 2.0 JTD 16V (88 KW) AUTOMATIC (2006-2011)

**ENGINE RHM**

Capacity: 5,25 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Emperol 5W-40***Change every 30000 km/ 12 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 4,5-6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032****HYDRAULIC BRAKE SYSTEM ABS**

Capacity: 0,52 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 30000 km, change every 60000 km/ 24 months***ELECTRO-HYDRAULIC POWER STEERING**

Capacity: 1,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Fluid 3013***Check every 30000 km***POWER STEERING**

Capacity: 1,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032***Check every 30000 km*

FIAT (EU) ULYSSE 179 ULYSSE 2.0 JTD 16V (88 KW) AUTOMATIC (2006-2011)

**COOLING SYSTEM**

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Check every 20000 km/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.