

# FIAT (EU) ULYSSE 220 ULYSSE 1.8i (1997-1999)



## ENGINE

Capacity: 4,75 liter, Capacity: 4,25 liter (+ airconditioning), Filter capacity: 0,25 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Check every 500 km, change every 15000 km*

### USE

Normal

### CLIMATE

Arctic

### PRODUCT RECOMMENDATION 1

**Duranza LSP 5W-30**

### PRODUCT RECOMMENDATION 2

**Asyntho 5W-30***Check every 500 km, change every 15000 km*

## TRANSAXLE MANUAL 5/1

Capacity: 2,2 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**SP Gear 5015**

### PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W***Check every 60000 km*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,6 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

### PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 500 km, change every 24 months*

## POWER STEERING

Capacity: 1,3 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Check every 15000 km*

# FIAT (EU) ULYSSE 220 ULYSSE 1.8i (1997-1999)

**COOLING SYSTEM**

Capacity: 8,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 500 km, change every 60000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*