

## FIAT (EU) UNO 146 UNO 70SX (1990-1995)

**ENGINE 146A8000**

Capacity: 4,05 liter, Filter capacity: 0,55 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40***Check every 500 km, change every 20000 km/ 12 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Check every 500 km, change every 20000 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90***Check every 20000 km, change every 120000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,37 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

## PRODUCT RECOMMENDATION 3

**Drauliquid DOT 3***Check every 500 km, change every 12 months***COOLING SYSTEM**

Capacity: 6,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 500 km, change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.