FORD (EU) C-MAX MK I C-MAX 2.0 16V LPG (2009-2010)



ENGINE SYDA Capacity: 4,3 liter, Capacity: 4,6 liter (Dry fill), Filter capacity: 0,4 liter					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Duranza ECO 5W-20	Duranza LSP 5W-30				
	1				

Change every 20000 km/ 12 months

TRANSAXLE MANUAL MTX75 5/1 Capacity: 1,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

Check every 20000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 20000 km, change every 24 months

POWER STEERING				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Fluid 3013				

Check every 20000 km/ 12 months

COOLING SYSTEM Capacity: 6,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF	
Check every 20000 km/ 12 months, change every 120 months			

FORD (EU) C-MAX MK I C-MAX 2.0 16V LPG (2009-2010)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.